






12 製品記号	DS10-J●■	DS10H-W○	DS15-W○																																																																		
	○内にはオリフィス径の記号、□内には定格電圧の記号が入ります。																																																																				
電磁弁	標準品	受注品	受注品																																																																		
	0.1、0.25、0.4、0.8MPa 水 空気 油 	CAC製 桃太郎 mini 蒸気 温水 	0.13、0.3、0.55、1.0MPa 水 空気 油 蒸気 CAC製 桃太郎 mini 																																																																		
	型式：DS-10型	型式：DS-10H型	型式：DS-15型																																																																		
POINT	小型・小容量、桃太郎ミニ																																																																				
標準仕様	作動	通電開																																																																			
	適用流体	水注1・空気・油（灯油・軽油程度）注2.	蒸気・温水	水注1・空気・油（灯油・軽油程度）注2・蒸気																																																																	
	流体温度	5～80℃	5～175℃（温水の場合100℃以下）	5～180℃（温水の場合100℃以下）																																																																	
	オリフィス径	◎：4mm、◎：5.5mm、◎：7mm、◎：10mm																																																																			
	適用圧力	MAX. 0.8、0.4、0.25、0.1MPa注3.		MAX. 1.0、0.55、0.3、0.13MPa注4.																																																																	
	流体粘度	50cSt以下																																																																			
	定格電圧	1：AC100V 50/60Hz 2：AC200V 50/60Hz	AC100V 50/60Hz☆	AC100/200V 50/60Hz AC110/220V 60Hz共用																																																																	
	保護構造	防塵・防滴・屋内用（屋外で使用する場合、端子箱を併用してください。防雨形となります。*1.*2.）																																																																			
	端接続	JIS Rcねじ																																																																			
	材質	CAC注2. 本体 SUS ディスク FKM																																																																			
価格(円)	呼び径	水・空気・油用	寸法L×H (mm)	梱包数 (質量)	蒸気・温水用	寸法L×H (mm)	梱包数 (質量)	オールマイティ	寸法L×H (mm)	梱包数 (質量)																																																											
			梱包質量 (kg)	質量 (kg)		梱包質量 (kg)	質量 (kg)		梱包質量 (kg)	質量 (kg)																																																											
	10	20,600	50×89 0.7	10 (11)	21,300	50×89 0.7	10 (11)	35,900	50×89 0.9	10 (13)																																																											
	15	20,900	56×91 0.7	10 (11)	21,800	56×91 0.7	10 (11)	35,900	56×91 0.9	10 (13)																																																											
20	21,500	63×95 0.8	10 (12)	22,000	63×95 0.8	10 (12)	35,900	63×96 1	10 (14)																																																												
記事	<p>☆AC200V 50/60Hzも製作しています。                  ※1.端子箱付は専用電圧となります。                  ※2.DS-15型のTB-03C型端子箱付は防沫形となります。                  ※3.共用電圧コイルの結線方法は146頁をご参照ください。                  注1.給水装置に使用する場合は、水道法性能基準適合品のDS-11N、11LN型、又はWS-22N型をご使用ください。（87頁参照）                  注2.燃料油、軽油用の場合はご使用先（国土交通省、防衛省など）によっては、本体材質の指定がある場合がありますので、ご確認の上、材質をご指示願います。</p>			<p>■価格加算</p> <table border="1"> <tr> <th>記号</th> <th>仕様</th> <th>加算額</th> </tr> <tr> <td>3-1</td> <td>屋外用TB-03型端子箱付</td> <td>7,400</td> </tr> </table> <p>*ご注文の際は、電圧・周波数をお知らせください。</p>	記号	仕様	加算額	3-1	屋外用TB-03型端子箱付	7,400																																																											
	記号	仕様	加算額																																																																		
3-1	屋外用TB-03型端子箱付	7,400																																																																			
<p>注3.適用圧力</p> <table border="1"> <tr> <th>オリフィス径の記号</th> <th>S</th> <th>H</th> <th>M</th> <th>L</th> </tr> <tr> <td>オリフィス径 (mm)</td> <td>4</td> <td>5.5</td> <td>7</td> <td>10</td> </tr> <tr> <td>最高使用圧力 (MPa)</td> <td>0.8</td> <td>0.4</td> <td>0.25</td> <td>0.1</td> </tr> <tr> <td rowspan="3">Cv値</td> <td>呼び径10</td> <td>0.45</td> <td>0.75</td> <td>1.1</td> </tr> <tr> <td>// 15</td> <td></td> <td></td> <td>2.1</td> </tr> <tr> <td>// 20</td> <td>0.45</td> <td>0.85</td> <td>1.3</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>2.2</td> </tr> </table>			オリフィス径の記号	S	H	M	L	オリフィス径 (mm)	4	5.5	7	10	最高使用圧力 (MPa)	0.8	0.4	0.25	0.1	Cv値	呼び径10	0.45	0.75	1.1	// 15			2.1	// 20	0.45	0.85	1.3					2.2	<p>注4.適用圧力</p> <table border="1"> <tr> <th>オリフィス径の記号</th> <th>S</th> <th>H</th> <th>M</th> <th>L</th> </tr> <tr> <td>オリフィス径 (mm)</td> <td>4</td> <td>5.5</td> <td>7</td> <td>10</td> </tr> <tr> <td>最高使用圧力 (MPa)</td> <td>1.0</td> <td>0.55</td> <td>0.3</td> <td>0.13</td> </tr> <tr> <td rowspan="3">Cv値</td> <td>呼び径10</td> <td>0.45</td> <td>0.75</td> <td>1.1</td> </tr> <tr> <td>// 15</td> <td></td> <td></td> <td>2.0</td> </tr> <tr> <td>// 20</td> <td>0.45</td> <td>0.85</td> <td>1.3</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>2.4</td> </tr> </table>	オリフィス径の記号	S	H	M	L	オリフィス径 (mm)	4	5.5	7	10	最高使用圧力 (MPa)	1.0	0.55	0.3	0.13	Cv値	呼び径10	0.45	0.75	1.1	// 15			2.0	// 20	0.45	0.85	1.3					2.4
オリフィス径の記号	S	H	M	L																																																																	
オリフィス径 (mm)	4	5.5	7	10																																																																	
最高使用圧力 (MPa)	0.8	0.4	0.25	0.1																																																																	
Cv値	呼び径10	0.45	0.75	1.1																																																																	
	// 15			2.1																																																																	
	// 20	0.45	0.85	1.3																																																																	
				2.2																																																																	
オリフィス径の記号	S	H	M	L																																																																	
オリフィス径 (mm)	4	5.5	7	10																																																																	
最高使用圧力 (MPa)	1.0	0.55	0.3	0.13																																																																	
Cv値	呼び径10	0.45	0.75	1.1																																																																	
	// 15			2.0																																																																	
	// 20	0.45	0.85	1.3																																																																	
				2.4																																																																	

端子箱 電磁弁に電源を接続する際に用いる端子箱です。	TB-03型	TB-03L型																						
																								
	<table border="1"> <tr> <th>型式</th> <th>製品記号</th> <th>仕様</th> <th>寸法AxB (mm)</th> <th>価格 (円)</th> </tr> <tr> <td>TB-03</td> <td>TB03-A</td> <td>屋外用</td> <td>69×84</td> <td>7,400</td> </tr> <tr> <td>TB-03C</td> <td>TB03C-A</td> <td>屋外用 (キャブコン付)</td> <td>69×117</td> <td>8,700</td> </tr> <tr> <td rowspan="2">TB-03L</td> <td>TB03L-A1</td> <td>屋外用 (ランプ付、AC100V)</td> <td rowspan="2">69×84</td> <td rowspan="2">10,800</td> </tr> <tr> <td>TB03L-A2</td> <td>屋外用 (ランプ付、AC200V)</td> </tr> </table>	型式	製品記号	仕様	寸法AxB (mm)	価格 (円)	TB-03	TB03-A	屋外用	69×84	7,400	TB-03C	TB03C-A	屋外用 (キャブコン付)	69×117	8,700	TB-03L	TB03L-A1	屋外用 (ランプ付、AC100V)	69×84	10,800	TB03L-A2	屋外用 (ランプ付、AC200V)	<p>*ご注文の際は、電磁弁型式・呼び径・電圧・周波数もお知らせください。                  ※電源定格 250V 15A（ランプ付はAC100V又は200V）                  注.雰囲気湿度85%を超える場合はお問い合わせください。</p>
型式	製品記号	仕様	寸法AxB (mm)	価格 (円)																				
TB-03	TB03-A	屋外用	69×84	7,400																				
TB-03C	TB03C-A	屋外用 (キャブコン付)	69×117	8,700																				
TB-03L	TB03L-A1	屋外用 (ランプ付、AC100V)	69×84	10,800																				
	TB03L-A2	屋外用 (ランプ付、AC200V)																						