

<div style="text-align: center; font-size: 2em; font-weight: bold;">3</div> 製品記号	SF1H-M□		SF2H-M□																					
	□内には圧力区分の記号が入ります。(下表参照)																							
<div style="text-align: center;">   <b>安全弁</b> </div>	受注品 全量式 1.6MPa (蒸気) (空気)		受注品 全量式 1.6MPa (蒸気) (空気)																					
	 型式：SF-1H型		 型式：SF-2H型																					
POINT 全量式 1.6MPa ねじ込形																								
標準仕様	形式	全量式																						
	キャップ形式	レバー付	レバー無																					
	適用流体	蒸気・空気																						
	流体温度	0~220℃																						
	設定圧力範囲	0.1~1.6MPa (設定圧力・流体名をお知らせください)																						
	端接続	入口：JIS Rねじ 出口：JIS Rcねじ																						
材質	本体	FCD																						
	弁体	SUS																						
	弁座	SUS (ステライト溶着)																						
呼び径※	ノド径 (mm)	レバー付	レバー無	寸法L <sub>1</sub> ×L <sub>2</sub> (mm)																				
価格 (円)	20	15	158,000	158,000	寸法L <sub>1</sub> ×L <sub>2</sub> (mm)																			
					梱包質量 (kg)																			
					50×75																			
					5.3																			
					60×85																			
25	19	191,000	191,000	7.2																				
				70×100																				
40	30	241,000	241,000	11.6																				
				85×115																				
50	38	319,000	319,000	18																				
				18																				
※呼び径と接続ねじ寸法は異なります。接続ねじ寸法は、呼び径の1サイズupとなります。																								
■圧力区分 (MPa)																								
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>記号</th> <th>圧力区分</th> <th>記号</th> <th>圧力区分</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>0.1~0.12</td> <td>5</td> <td>0.5を超え0.75</td> </tr> <tr> <td>2</td> <td>0.12を超え0.2</td> <td>6</td> <td>0.75を超え1.0</td> </tr> <tr> <td>3</td> <td>0.2を超え0.3</td> <td>7</td> <td>1.0を超え1.3</td> </tr> <tr> <td>4</td> <td>0.3を超え0.5</td> <td>8</td> <td>1.3を超え1.6</td> </tr> </tbody> </table>					記号	圧力区分	記号	圧力区分	1	0.1~0.12	5	0.5を超え0.75	2	0.12を超え0.2	6	0.75を超え1.0	3	0.2を超え0.3	7	1.0を超え1.3	4	0.3を超え0.5	8	1.3を超え1.6
記号	圧力区分	記号	圧力区分																					
1	0.1~0.12	5	0.5を超え0.75																					
2	0.12を超え0.2	6	0.75を超え1.0																					
3	0.2を超え0.3	7	1.0を超え1.3																					
4	0.3を超え0.5	8	1.3を超え1.6																					

<div style="text-align: center; font-size: 2em; font-weight: bold;">3</div> 名称	温度圧力安全弁			
	受注品			
<div style="text-align: center;">                   アメリカ                  ワッツ社製                  温度圧力安全弁             </div>	 (水) (温水)			
	POINT 温度又は圧力超過対策に			
標準仕様	呼び径	¾~2 (20~50)		
	適用流体	水・温水		
	逃し温度	210°F (98.9℃)		
	標準設定圧力	75、100、125、150PSI		
	端接続	NPTねじ		
注.呼び径、設定圧力は製品により異なります。詳細はお問い合わせください。				
別途お見積り致します。				